

## Technical Information

## ACCUREL® Si 754

ACCUREL® Si 754 is a 12500 cSt silicone oil on a porous high-density polyethylene (HDPE) carrier.

## Physical Properties

Melt temperature	Approx. 120 °C
Bulk density	200 – 250 kg/m <sup>3</sup>
Colour	White/off-white
Delivery form	Pellets
Additive Content	50 (± 2) wt%

## Application

ACCUREL® Si 754 acts as a fast and effective lubricant and mold release agent for HDPE based parts.

The pre-dispersion of the silicone oil in the porous carrier supports a homogeneous distribution of the silicone oil in the finished product.

ACCUREL® Si 754 allows a fast and long-lasting lubricating effect on the finished components.

## Benefits

- easy handling of highly viscous silicone oil as a solid
- fast and long lasting lubricating effect
- efficient mold release

## Dosage

ACCUREL® Si 754 can be incorporated using gravimetric or volumetric dosing equipment or by pre-blending it with the base resin.

The recommended level of addition for ACCUREL® Si 754 is in the range of

- 0.2 – 0.4 % as mold release agent
- 0.5 – 1.0 % as lubricant

## Food Contact Status

ACCUREL® Si 754 complies with the EU and FDA food contact regulations.

## Registration

ACCUREL® Si 754 complies with REACH Regulation (EC) No 1907/2006.

Its ingredients of ACCUREL® Si 754 are listed / comply with the following chemical inventories:

EINECS, TSCA, DSL, ENCS, AICS, TCCL, PICCS, IECS, NZOIC, TCSI

## Storage Stability

Minimum 12 months after date of production under normal good storing conditions.

## Packaging

12 kg net in a cardboard box with PE inliner  
216 kg net (18 x 12 kg) on Euro-Pallet

## Product Safety

For transport, handling and first aid instructions we refer to the material safety data sheet for ACCUREL® Si 754.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

**Evonik Nutrition & Care GmbH**  
Goldschmidtstraße 100  
45127 Essen, Germany  
Phone Europe +49 201 173 2665  
Phone Asia +86 21 61191 125  
Phone Americas +1 804 727 0700  
[interface-performance@evonik.com](mailto:interface-performance@evonik.com)  
[www.evonik.com/interface-performance](http://www.evonik.com/interface-performance)