

Technical Information

ACCUREL® XP 650

ACCUREL® XP 650 is a porous carrier resin made from PMMA.

Physical Properties

Melt temperature	> 200 °C
Bulk density	100 – 140 kg/m ³
Maximum loading capacity	50 %
Colour	White/off-white
Delivery form	Pellets
Pellet size	2 – 4 mm

Application

ACCUREL® XP 650 is a porous PMMA carrier for the production of additive concentrates at loading temperatures up to 80°C via physical absorption of the additive.

ACCUREL® XP 650 is most effective for the incorporation of thermally sensitive additives and for those which cannot be processed by conventional extrusion compounding techniques.

In general, additive viscosity should not exceed 30,000 cSt at absorption processing temperature.

Benefits

- up to 50 % additive content
- no additional heat history for the additive
- pre-dispersed additive in the porous structure of the carrier resin
- dosage like conventional masterbatches

Additive Absorption Process

For details concerning how to load ACCUREL® XP 650 pellets please contact us.

Food Contact Status

ACCUREL® XP 650 complies with the EU and FDA food contact regulations.

Registration Status

ACCUREL® XP 650 complies with REACH Regulation (EC) No 1907/2006.

The ingredients of ACCUREL® XP 650 are listed/comply with the following chemical inventories:

EINECS

Storage Stability

60 months after date of production under normal good storing conditions.

Packaging

Cardboard boxes with LDPE inliner
Net weight per box: to be determined
4 resp. 8 boxes on a pallet

Product Safety

For transport, handling and first aid instructions we refer to the material safety data sheet for ACCUREL® XP 650.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Evonik Nutrition & Care GmbH
Goldschmidtstraße 100
45127 Essen, Germany
Phone Europe +49 201 173 2665
Phone Asia +86 21 61191 125
Phone Americas +1 804 727 0700
interface-performance@evonik.com
www.evonik.com/interface-performance