

## Technical Information

## ACCUREL® SF 271

ACCUREL® SF 271 is a mixture of antistatic and slip agents with polypropylene homopolymer.

## Physical Properties

Melt temperature	approx. 160 °C
Bulk density	400 – 600 kg/m <sup>3</sup>
Colour	Off-white/creamy
Delivery form	Pellets
Additive Content	65 (± 2) wt%

## Application

ACCUREL® SF 271 is a synergistic combination of slip and antistatic additives for biaxial oriented polypropylene (BOPP) films, such as general-purpose films, adhesive and paper lamination films.

## Benefits

- short and long term antistatic performance
- reduced surface coefficient of friction (COF)
- suitable for transparent applications

## Dosage

ACCUREL® SF 271 can be incorporated using gravimetric or volumetric dosing equipment or by pre-blending it with the base resin.

The recommended level of addition for ACCUREL® SF 271 is in the range of

- 0.6 – 1.2 % in the film core layer
- 0.2 – 0.4 % for food contact applications

## Food Contact Status

ACCUREL® SF 271 complies with the EU and FDA food contact regulations with restrictions.

## Registration Status

ACCUREL® SF 271 complies with REACH Regulation (EC) No 1907/2006.

The ingredients of ACCUREL® SF 271 are listed / comply with the following chemical inventories:

EINECS, TCCL, PICCS, IECS, NZIOC, TCSI

## Storage Stability

12 months after date of production under normal good storing conditions.

## Packaging

30 kg net in a cardboard box with PE inliner  
720 kg net (24 x 30 kg)

## Product Safety

For transport, handling and first aid instructions we refer to the material safety data sheet for ACCUREL® SF 271.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

**Evonik Nutrition & Care GmbH**  
Goldschmidtstraße 100  
45127 Essen, Germany  
Phone Europe +49 201 173 2665  
Phone Asia +86 21 61191 125  
Phone Americas +1 804 727 0700  
[interface-performance@evonik.com](mailto:interface-performance@evonik.com)  
[www.evonik.com/interface-performance](http://www.evonik.com/interface-performance)